



INDUCTIVE PROXIMITY SWITCH				
Outward appearance code		LM30		
Appearance				
Dimension				
Flush	Detection distance		10mm	
	DC 6	NPN	NO	3010NA
			NC	3010NB
			NO+NC	3010NC
	~ 36	PNP	NO	3010PA
			NC	3010PB
			NO+NC	3010PC
	V	two wire system	NO	3010LA
			NC	3010LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2010A
			NC	2010B
			NO+NC	2010C
Relay output		2010JC		
Non-flush	Detection distance		15mm	
	DC 6	NPN	NO	3015NA
			NC	3015NB
			NO+NC	3015NC
	~ 36	PNP	NO	3015PA
			NC	3015PB
			NO+NC	3015PC
	V	two wire system	NO	3015LA
			NC	3015LB
	AC 90 ~ 250 V	SRC Control label silicon	NO	2015A
			NC	2015B
			NO+NC	2015C
Relay output		2015JC		
Control output	DC		200mA	
	SCR/Relay		300mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		30×30×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		200Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		Metal		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		E2E-X18M□		