



INDUCTIVE PROXIMITY SWITCH				
Structural category		Angular column type		
Outward appearance code		<b>LMF10</b>		
Appearance				
Dimension				
Flush	Detection distance		15mm	
	DC 6 ~ 36 V	NPN	NO	3015NA
			NC	3015NB
			NO+NC	3015NC
	PNP	NO	3015PA	
		NC	3015PB	
		NO+NC	3015PC	
	two wire system	NO	3015LA	
		NC	3015LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2015A
			NC	2015B
			NO+NC	
Relay output				
Non-Flush	Detection distance		20mm	
	DC 6 ~ 36 V	NPN	NO	3020NA
			NC	3020NB
			NO+NC	3020NC
	PNP	NO	3020PA	
		NC	3020PB	
		NO+NC	3020PC	
	two wire system	NO	3020LA	
		NC	3020LB	
	AC 90 ~ 250 V	SRC Control label silicon	NO	2020A
			NC	2020B
			NO+NC	
Relay output				
Control output	DC		300mA	
	SCR/Relay		500mA	
Output voltage dropDC/AC		DC<3V AC<10V		
Consumption current		DC<15mA AC<10mA		
Standard detected object		45×45×1(A3 iron)		
Repeated precision		0.05		
DC/AC Response frequency		100Hz/25Hz		
Working environment temperature		-25℃~75℃		
Insulation resistance		50MΩ		
Shell material		ABS Resin		
Protection grade		IEC standard IP67		
Alternative model at home and abroad		TL-N20M□		